




Model:		<div>AP-A6XM-3MP</div> <div>3MP Camera (No TF Card) X 1 * DC 12V 1A power adapter X1 * Instructions X1 * Screw bag X1</div> <div></div>	
Specification parameter			
system	Main Processor	Dual-core 32-bit DSP (GK7202V300), pure hard compression, watchdog	
	image sensor	High performance CMOS sensor	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	3MP	
	resolution ratio	Main stream: 2304*1296@12fps; Substream: 800*448@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
	Lens	3.6mm	
	Humanoid tracking	support	
	Turn video	Flip up and down/flip left and right	
	Video Compression	H.265AI	
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°	
	Turn PTZ	Flip up and down/flip left and right	
Audio	Coding standard	G.711	
	Two-way voice	support	
	Mitou	support	
	loudspeaker	support	
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (128GB Max)	
	Remote playback	support	
	Image capture	support	
Network	network port	10M/100M adaptive Ethernet port	
	WIFI	2.4G IEEE 802.11 b/g/n/ax	
	Connect APP	Bluetooth connection, scan code connection	
	ONVIF	support	
extension	Reset key	support	
	LED	8LED	
	Power	DC 12V	
work environment	Suitable place	outdoor、Home、shop、School、factory;	
	Installation mode	Wall hanging	
	Working	-10℃ — +55℃	
	Working humidity	10% — 90%	

Model: <div> AP-A6XM-4MP </div>		*4MP PTZ camera (without TF card) X 1 * Instruction manual X1 * Screw pack X1 * Power adapter X1	
Specification parameter			
system	Main Processor	Dual-core 32-bit DSP (GK7205V210), pure hard compression, watchdog	
	image sensor	1/2.8 inch high performance CMOS sensor	
	Operation System	Embedded LINUX operating system	
	Video Compression	H.265AI	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	4MP	
	Image resolution	Main code stream: 2560*1440@12fps; Substream: 640*360@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
	Lens	3.6mm	
	Turn video	Flip up and down/flip left and right	
lighting	Light control mode	Starlight full color/intelligent warning/infrared night vision	
	Number of lights	4 red lights + 4 white lights	
PTZ	PTZ control	Rotation Angle level :340°; Vertical :90°	
	Turn PTZ	Flip up and down/flip left and right	
Audio	Coding standard	G.711	
	Mitou	support	
	Two-way Speech	support	
Record management	Video file size	Hd video ≈20 G/ day SD video ≈2.4 G/ day	
	Record Mode	Manual video recording, dynamic detection video recording, alarm video	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (128GB Max)	
	Remote playback	support	
	Image capture	support	
Network	network port	10M/100M adaptive Ethernet port	
	WIFI	2.4G WIFI 802.11b/g/n	
	Pairing	iFi Smartlink distribution network addition, AP hotspot addition, QR code scanning	
	ONVIF	support	
extension	Reset key	support	
	Human tracking	support	
	Power	DC 12V	
work environment	Suitable place	outdoor、Home、shop、School、factory;	
	Installation mode	Wall hanging	
	Working	-20℃ — + 55℃	
	Working humidity	10% — 90%	

Model:		
<div>AP-A6XM-8MP</div>		*8MP PTZ camera (without TF card) X 1 * Instruction manual X1 * Screw pack X1 * Power adapter X1
		
Specification parameter		
system	Main Processor	Dual-core 32-bit DSP (NT98566), pure hard compression, watchdog
	image sensor	1/2.7 inch high performance CMOS sensor
	Operation System	Embedded LINUX operating system
	Video Compression	H.265AI
	APP	ICSEE (Android and IOS support)
Video	High Definition	8MP
	Image resolution	Main code stream: 2560*1440@12fps; Substream: 640*360@12fps
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	Lens	3.6mm
	Turn video	Flip up and down/flip left and right
lighting	Light control mode	Starlight full color/intelligent warning/infrared night vision
	Number of lights	4 red lights +4 white lights
PTZ	PTZ control	Rotation Angle level :340°; Vertical :90°
	Turn PTZ	Flip up and down/flip left and right
Audio	Coding standard	G.711
	Mitou	support
	Two-way Speech	support
Record management	Video file size	Hd video ≈20 G/ day SD video ≈2.4 G/ day
	Record Mode	Manual video recording, dynamic detection video recording, alarm video
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (128GB Max)
	Remote playback	support
	Image capture	support
Network	network port	10M/100M adaptive Ethernet port
	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	AP hotspot addition, QR code scanning
	ONVIF	support
extension	Reset key	support
	Human tracking	support
	Power	DC 12V
work environment	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging
	Working	-20℃ — +55℃
	Working humidity	10% — 90%