AP-B313**-WD-TG81B**

8MP Camera (No TF Card) X 1

- * DC 5V 1A power adapter X1
- * power cord X1
- * Instructions X1
- * Screw bag X1



| Specification parameter | | |
|-------------------------|------------------------|--|
| system | Main Processor | FH8856V310 |
| | image sensor | High performance CMOS image sensor |
| | APP | TUYA |
| | Effective video pixels | 8MP |
| | resolution ratio | Main stream: 3840×2160; Sub stream: 640 × 360 |
| | Lens | 3.6mm |
| | Image encoding | H.265 |
| | Rotation angle | Horizontal: 355 °; Vertical: 90 ° |
| Video | Light control mode | Starlight Full Color/Infrared Night Vision/Dual Light Alert |
| | Humanoid tracking | support |
| | Screen flipping | support |
| | Privacy mode | support |
| | Buzzer linkage | support |
| | Sound detection | support |
| | Coding standard | G.711A |
| Audio | Two-way voice | support |
| Addio | Mitou | support |
| | loudspeaker | support |
| | Record Mode | Manual recording, dynamic detection recording, alarm recording |
| Decemb | Video storage | TF Card/Cloud |
| Record management | storage | Cloud storage+TF local recording (maximum support of 128GB) |
| | Remote playback | support |
| | Image capture | support |
| | WIFI | 2.4G |
| Network | Connect APP | Bluetooth connection, pairing connection |
| | ONVIF | support |
| | Reset key | support |
| extension | lamp panel | 2 pcs |
| | Power | DC5V |
| work environment | Suitable place | Places such as homes, shops, supermarkets, factories, etc; |
| | Installation mode | Wall hanging |
| | Working | -20 °C − +55°C |
| | Working humidity | 10%-90% |

AP-B313-**W-TG31B**

3MP Camera (No TF Card) X 1

- * DC 5V 1A power adapter X1
- * 1 m power cord X1
- * Bracket X1
- * Instructions X1
- * Screw bag X1



| Specification parameter | | |
|-------------------------|------------------------|--|
| system | Main Processor | FH8626V200 |
| | image sensor | High performance CMOS image sensor |
| | APP | TUYA |
| | Effective video pixels | 3MP |
| | resolution ratio | Main stream: 2304 × 1296; Sub stream: 640 × 360 |
| | Lens | 3.6mm |
| | Image encoding | H.265 |
| | Rotation angle | Horizontal: 355 °; Vertical: 90 ° |
| Video | Light control mode | Starlight full color/intelligent warning/infrared night vision |
| | Humanoid tracking | support |
| | Screen flipping | support |
| | Privacy mode | support |
| | Buzzer linkage | support |
| | Sound detection | support |
| | Coding standard | G.711A |
| Adi.a | Two-way voice | support |
| Audio | Mitou | support |
| | loudspeaker | support |
| | Record Mode | Manual recording, dynamic detection recording, alarm recording |
| | Video storage | TF Card/Cloud |
| Record management | storage | Cloud storage+TF local recording (maximum support of 128GB) |
| managomont | Remote playback | support |
| | Image capture | support |
| | WIFI | 2.4G |
| Network | Connect APP | Bluetooth connection, pairing connection |
| | ONVIF | support |
| | Reset key | support |
| extension | lamp panel | 2LED |
| | Power | DC5V |
| | Suitable place | Places such as homes, shops, supermarkets, factories, etc; |
| work environment | Installation mode | Wall hanging, lifting, and laying flat |
| work environment | Working | -20 ℃−+55℃ |
| | Working humidity | 10%-90% |

AP-B313-**W-TG32B**

- * 3MP Camera (No TF Card) X 1
- * DC 5V Power adaptor x 1
- * USB cable X1
- * Instructions X1
- * Screw bag X1



| Specification parameter | | |
|-------------------------|--|--|
| | Main Processor | FH8616+1084/ 2.4G+bluetooth connection |
| | System security | TUYA intelligent cloud platform, financial level security system |
| | Supports IOS and Android operating systems | Multi-language, multi-category, universal, do not need to worry about mobile phone adaptation, support OEM and ODM customization |
| System | Local storage | Support 8-128GB MicroSD card, 24 hours video recording. |
| characteristics | Remote online upgrade | Easily realize remote OTA online upgrade through TUYA cloud, and experience the latest version in the first time |
| | Value-added service | Support TUYA cloud storage function, optionally open Amazon Echo/ Google Chromecast service |
| | Operation System | Embedded LINUX OS system |
| | High Definition | 3MP (2048X1536) |
| | Video Compression | Smart H.264 main profile5.0 |
| | Illumination | 0.02Lux@(2.0AGC ON).OLUX with IR |
| Video | Frame frequency | Main stream (HD) : 2048×1536@15fps Substream (SD) : 640*480@10fps |
| | picture Capture | Support |
| | Led Board | 2 DUAL LEDS |
| | Len | 3.6mm |
| Audia | Coding standard | G.711 |
| Audio | Two-way talking | Support |
| | Mirror/flip | support |
| | Noise reduction/dynamic range | 3D Noise reduction /72DB |
| | Motion tracking | support |
| | Voice intercom | Support two-way voice intercom, echo elimination |
| | Audio input | 1-way MIC |
| | Audio output | 1 way Speaker (8 ohm 1W/2W/4W) |
| | Night vision mode | IR-CUT Switches automatically |
| Basic function | WIFI connection | 2.4G, |
| | Wired connection | optional |
| | Adding mode | Support QR code scanning, Wifi mode |
| | Network protocol | DHCP |
| | Motion detection | support |
| | Restore default | support |
| | Local storage | TF card is supported to store continuous video/event video, the maximum support is 128G TF card |
| Value-added service | Doodle cloud storage | Supports continuous video recording or event recording |
| | Amazon Alexa | Support (optional) |
| | Google assistant | Support (optional) |
| | Power supply specification | DC 5V 1A |
| other | PCB size | Mainboard (50)mm |
| work | Suitable place | Home,shop,School,factory |
| | Working Temperature | -10°C −60°C |
| | Working humidity | 10% ~ 95% non-condensing |

AP-B313**-W-TG41B**

- 1. 2K 4mp 8852V201+3003 1/3 inch sensor
- 2. 2.4G+Bluetooth Connection, Onvif
- 3.Smart AI function: AI-human shape alarming, No

False alarm.

4.Pet detection: Detect cat and dog, record and


notice information

- * 4MP Camera (No TF Card) X 1
- * DC 5V 1A power adapter X1
- * power cord X1
- * Instructions X1
- * Screw bag X1



| lotice information | Spec | ification parameter |
|--------------------|------------------------|--|
| system | Main Processor | FH8852V201 |
| | image sensor | High performance CMOS image sensor |
| | APP | TUYA |
| | Effective video pixels | 4MP |
| | resolution ratio | Main stream:2688×1520; Sub stream: 640 × 360 |
| | Lens | 3.6mm |
| | Image encoding format | H.265 |
| | Rotation angle | Horizontal: 355 °; Vertical: 90 ° |
| Video | Light control mode | Starlight Full Color/Infrared Night Vision/Dual Light Alert |
| | Humanoid tracking | support |
| | Screen flipping | support |
| | Privacy mode | support |
| | Buzzer linkage | support |
| | Sound detection | support |
| | Coding standard | G.711A |
| | Two-way voice | support |
| Audio | Mitou | support |
| | loudspeaker | support |
| | Record Mode | Manual recording, dynamic detection recording, alarm recording |
| | Video storage | TF Card/Cloud |
| Record management | storage | Cloud storage+TF local recording (maximum support of 128GB) |
| management | Remote playback | support |
| | Image capture | support |
| | WIFI | 2.4G |
| Network | Connect APP | Bluetooth connection, pairing connection |
| | ONVIF | support |
| | Reset key | support |
| extension | lamp panel | Infrared light: 4pcs, white light: 4pcs |
| | Power | DC5V |
| | Suitable place | Places such as homes, shops, supermarkets, factories, etc; |
| | Installation mode | Wall mount/Ceiling mount/ Flat |
| vork environment | Working Temperature | -20℃−+55℃ |
| | Working humidity | 10%-90% |

AP-B313**-W-TG51B**



- * DC 5V power adapter X1
- * 1 m power cord X1
- * Round Bracket X1
- * Instructions X1
- * Screw bag X1



| | S | pecification parameter |
|---------------------------|----------------------------|---|
| System characteristics | Chipset | FH8636+MIS4001 2.4G +Bluetooth connection+AI-human shape detection |
| | image sensor | High performance CMOS image sensor |
| | APP | TUYA |
| | High Definition | 5MP (2880×1620) |
| | Video Compression | Smart H.265 |
| | Rotation angle | Horizontal:355°; vertical: 90° |
| | Object tracking | Support |
| Video | Illumination | 0.02Lux@(2.0AGC ON).OLUX with IR |
| Video | Frame frequency | Main stream (HD) : 2880×1620 Substream (SD) : 640*360 |
| | picture Capture | Support |
| | Led Board | 6 IR LEDS |
| | Len | 3.6mm |
| a | Coding standard | G.711 |
| Audio | Two-way talking | Support |
| | Mirror/flip | support |
| | Noise reduction/dynamic | 3D Noise reduction /72DB |
| | Motion tracking | support |
| | Voice intercom | Support two-way voice intercom, echo elimination |
| | Audio input | 1-way MIC |
| | Audio output | 1 way Speaker (8 Ω 1W/2W/4W) |
| | Night vision mode | IR-CUT Switches automatically |
| Basic function | WIFI connection | 2.4G, |
| | Wired connection | optional |
| | Adding mode | Support QR code scanning, Wifi mode. |
| | Network protocol | DHCP, ONVIF |
| | Motion detection | support |
| | Restore default | support |
| | Local storage | TF card is supported to store continuous video/event video, the maximum support is 128G TF card |
| | Tuya cloud storage | Supports continuous video recording or event recording |
| Value-added service | Amazon Alexa | Support (optional) |
| | Google assistant | Support (optional) |
| ath ar | Power supply specification | 5V 1A |
| other | PCB size | Mainboard (L38*W52.5*H1.6)mm |
| | Suitable place | Home,shop,School,factory |
| work environment | Working Temperature | -10℃—60℃ |
| | Working humidity | 10% ~ 95% non-condensing |

AP-B313-W-TG61B

- * 6MP Camera (No TF Card) X 1 * DC 5V 1A power adapter X1
- * 1 m power cord X1
- * Bracket X1
- * Instructions X1
- * Screw bag X1



| | Sp | ecification parameter |
|-----------------|--|--|
| System | Main Processor | 6MP FH8856V310+4653 2.4G+Bluetooth connection+Al-human shape alarming |
| | Image sensor | 1/2.9 3.0M Pixel Progressive Scan CMOS |
| | System security | TUYA intelligent cloud platform, financial level security system |
| | Supports IOS and Android operating systems | Multi-language, multi-category, universal, do not need to worry about mobile phone adaptation, support OEM and ODM |
| characteristics | Local storage | Support 8-128GB MicroSD card, 24 hours video recording. |
| | Remote online upgrade | Easily realize remote OTA online upgrade through TUYA cloud, and experience the latest version in the first time |
| | Value-added service | Support TUYA cloud storage function, optionally open Amazon Echo/ Google Chromecast service |
| | Operation System | Embedded LINUX OS system |
| | High Definition | 6MP 3200*1800@25FPS |
| | Video Compression | Smart H.265/H.264 |
| | Illumination | 0.02Lux@(2.0AGC ON).OLUX with IR |
| Video | Frame frequency | Main stream (HD) :3200*1800@25fps Substream (SD) : 640*360@10 fps |
| | picture Capture | Support |
| | Led Board | 2 Dual LEDS |
| | Len | 3.6mm |
| Audio | Coding standard | G.711 |
| Audio | Two-way talking | Support |
| | Mirror/flip | support |
| | Noise reduction/dynamic range | 3D Noise reduction /72DB |
| | Motion tracking | support |
| | Voice intercom | Support two-way voice intercom, echo elimination |
| | Audio input | 1-way MIC |
| | anti-flicker | Supports outdoor, 50 Hz, and 60Hz |
| | Indicator light | Network port indicator |
| Danie ferration | Audio output | 1 way Speaker (8 Ohms 1W/2W/4W) |
| Basic function | Night vision mode | IR-CUT Switches automatically |
| | WIFI connection | 2.4G |
| | Wired connection | Support |
| | Adding mode | Support QR code scanning, Wifi mode. Wired connection |
| | Network protocol | DHCP |
| | Motion detection | support |
| | Restore default | support |