


Model: <div> AP-B326-W-S-4MP </div>		*2*2.0MP WIFI Dual-lens PTZ camera (excluding TF Card) X 1 * Specification X1 * Screw pack X1 * stents X1 * Power adapter X1 * Power cord X1 
Specification parameter		
system	Main Processor	Anyka
	image sensor	1/4.6" CMOS Sensor*2
	Operation System	Embedded LINUX operating system
	Video Compression	H.264/H.265
	APP	suniseePro
Video	High Definition	2+2MP
	Image resolution	Main code stream: 1920*2160@12fps; Substream: 640*720@12fps
	Wide dynamic range	support
	Lens	3.6mm
	Turn video	Flip up and down/flip side to side
lighting	Light control mode	infrared night vision
	Number of lights	6LED
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°
	Turn PTZ	Flip up and down/flip side to side
Audio	Coding standard	G.711
	Mitou	support
	Two-way Speech	support
Record management	Video file size	Hd video ≈9.7G/ day SD video ≈2.4G/ day
	Record Mode	Manual video recording, dynamic detection video recording, alarm video
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (256GB Max)
	Remote playback	support
	Image capture	support
Network	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	Bluetooth distribution network, AP hotspot addition, QR code scanning
extension	Reset key	support
	Human tracking	support
power supply	Power	DC 5V
	power interfac	Type-c
work environment	Suitable place	outdoor, Home, shop, School, factory;
	Installation mode	Wall hanging, lifting, flat
	Working Temperature	-10℃ — +55℃
	Working humidity	10% — 90%