


| | | | |
|--|----------------------|--|---|
| <div>Model:</div> <div>AP-B326-W-TY41 AP-B326-WD-TG81B</div> | | <div>*2*2.0MP WIFI Dual-lens PTZ camera (excluding TF Card) X 1</div> <div>* Specification X1</div> <div>* Screw pack X1</div> <div>* Power adapter X1</div> <div>* Power cord X1</div> <div></div> | |
| Specification parameter | | | |
| system | Chipset | 1/2.8" XM650V200+223 High performance CMOS sensors | 1/2.8" 8856V310+3003 High performance CMOS sensors |
| | Operation System | Embedded LINUX operating system | |
| | Video Compression | H.265 | |
| | APP | TUYA | |
| Video | High Definition | 2MP+2MP | 4MP+4MP |
| | Image resolution | Main code stream: 1920*2160@12fps； Substream: 800*896@12fps | |
| | Minimum illumination | 0.01 LUX/pro series | |
| | Lens | 3.6mm+3.6mm | |
| | Turn video | support | |
| lighting | Light control mode | infrared night vision | |
| | Number of lights | 10 red lights | |
| Audio | Coding standard | G.711 | |
| | Mitou | support | |
| | Two-way Speech | support | |
| Record management | Record Mode | Manual video recording, dynamic detection video recording, alarm video | |
| | Video storage | TF card/cloud | |
| | storage | Cloud Storage +TF Local Video recording (128GB Max) | |
| | Remote playback | support | |
| | Image capture | support | |
| Network | WIFI | 2.4G WIFI 802.11b/g/n | |
| | Pairing | AP hotspot addition, QR code scanning | |
| | Network Protocol | TCP/IP, RTSP | |
| extension | Reset key | support | |
| | PTZ control | Rotation Angle level :355°; Vertical :90° | |
| | Human tracking | support | |
| power supply | Power | DC 5V | |
| | power interfac | Type-c | |
| work environment | Suitable place | Home, shop, School, factory | |
| | Installation mode | Wall hanging, lifting, flat | |
| | Working Temperature | -20℃ — +55℃ | |
| | Working humidity | 10% — 90% | |