

<b>Model:</b>  <div style="background-color: #00C090; color: white; padding: 5px; border-radius: 10px; margin-top: 10px;"> <b>AP-B326-W-X41B</b>  <b>AP-B326-WX41S (Starlight Full Color)</b> </div>	<ul style="list-style-type: none"> <li>*2*2.0MP WIFI Dual-lens PTZ camera (excluding TF Card)</li> <li>* Specification X1</li> <li>* Screw pack X1</li> <li>* stents X1</li> <li>* Power adapter X1</li> <li>* Power cord X1</li> </ul>	
--	---	---

### Specification parameter

<b>system</b>	Main Processor	dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog
	image sensor	2 *1/4" high performance CMOS sensors
	Operation System	Embedded LINUX operating system
	Video Compression	H.265AI
	APP	ICSEE (Android and IOS support)
<b>Video</b>	High Definition	2+2MP
	Image resolution	Main code stream: 1920*2160@12fps; Substream: 640*720@12fps
	Minimum illumination	0.01 LUX/pro series
	Lens	3.6mm
	Turn video	Flip up and down/flip side to side
<b>lighting</b>	Light control mode	Starlight full color/intelligent warning/infrared night vision
	Number of lights	6LED
<b>PTZ</b>	PTZ control	Rotation Angle level :355°; Vertical :90°
	Turn PTZ	Flip up and down/flip side to side
<b>Audio</b>	Coding standard	G.711
	Mitou	support
	Two-way Speech	support
<b>Record management</b>	Video file size	Hd video ≈9.7G/ day      SD video ≈2.4G/ day
	Record Mode	Manual video recording, dynamic detection video recording, alarm
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (128GB Max)
	Remote playback	support
	Image capture	support
<b>Network</b>	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	Bluetooth distribution network, AP hotspot addition, QR code scanning
<b>extension</b>	Reset key	support
	Human tracking	support
<b>power supply</b>	Power	DC 5V
	power interfac	Type-c
<b>work environment</b>	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging, lifting, flat
	Working	-10℃ – +55℃
	Working humidity	10% – 90%