Model: AP-FY003-W-X41B AP-FY003-W-X41S(Starlight Full Color)		 * stents X1 * Power adapter X1 * Power cord X1 	
	Specification parameter		
I –		ual-core 32-bit DSP (XM650V200), pure hard compression, watchdo	
	nage sensor	2 *1/4" high performance CMOS sensors	
	peration System	Embedded LINUX operating system	
Vi	ideo Compression	H.265AI	
AF	PP	ICSEE (Android and IOS support)	
Hi	igh Definition	2+2MP	
Im	nage resolution	Main code stream: 1920*2160@12fps; Substream: 640*720@12fps	
Video Mi	inimum illumination	0.01 LUX/pro series	
Le	ens	3.6mm	
Τι	urn video	Flip up and down/flip side to side	
Lighting	ght control mode	Starlight full color/intelligent warning/infrared night vision	
lighting Nu	umber of lights	6LED	
	TZ control	Rotation Angle level :355°; Vertical :90°	
ΡΤΖ Τι	urn PTZ	Flip up and down/flip side to side	
Co	oding standard	G.711	
Audio Mi	itou	support	
Т	wo-way Speech	support	
Vi	ideo file size	Hd video \approx 9.7G/ day SD video \approx 2.4G/ day	
Re	ecord Mode	Manual video recording, dynamic detection video recording, alarm	
Record Vi	ideo storage	TF card/cloud	
	orage	Cloud Storage +TF Local Video recording (128GB Max)	
Re	emote playback	support	
Irr	nage capture	support	
w	/IFI	2.4G WIFI 802.11b/g/n	
Network	airing	luetooth distribution network, AP hotspot addition, QR code scannin	
Re	eset key	support	
extension –	uman tracking	support	
	ower	DC 5V	
power supply	ower interfac	Туре-с	
	uitable place	outdoor、Home、shop、School、factory;	
	stallation mode	Wall hanging, lifting, flat	
work environment	/orking	-10°C−+55°C	
	orking humidity	10%-90%	