


<b>Model:</b> <div> AP-P13-QQ9-AF-8X </div>		*3*3MP PTZ camera (without TF card) X 1 * Instruction manual X1 * Power adapter X1 * Screw pack X1	
Specification parameter			
system	Main Processor	dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog	
	image sensor	Two 1/3 "low illumination CMOS sensors	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	3*3MP	
	Image resolution	Main stream: 2304*2592@12fps; Substream: 640*720@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
	Lens	4mm+2.8mm	
	Humanoid tracking	support	
	Gun-ball linkage	support	
	Turn video	Flip up and down/flip left and right	
	Video Compression	H.265AI	
	Light control mode	Starlight full color/infrared night vision/double light alert	
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°	
	Turn PTZ	Flip up and down/flip left and right	
Audio	Coding standard	G.711	
	Two-way voice	support	
	Mitou	support	
	loudspeaker	support	
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (128GB Max)	
	Remote playback	support	
	Image capture	support	
Network	WIFI	2.4G IEEE 802.11 b/g/n Wi-Fi compliant	
	network port	10M/100M adaptive Ethernet port	
	Connect APP	Bluetooth connection, scan code connection	
extension	Reset key	support	
	Power	DC 12V±10%	
	LED	Gun mechanism: 4-light dual core, ball mechanism: 4 light dual core	
work environment	Suitable place	outdoor、Home、shop、School、factory:	
	Installation mode	Wall hanging, lifting	
	Working	-20℃ — +55℃	
	Working humidity	10% — 90%	