

Model:		<ul style="list-style-type: none"> *4MP 4G battery camera (without TF card) X 1 * Instruction manual X1 * Screw pack X1 * Bracket X1 * 3 m power cord X1 	
<div style="border: 1px solid black; border-radius: 15px; background-color: #00C090; color: white; padding: 10px; display: inline-block;"> AP-Q012B-4GL-X41-B-E </div>			
AP-Q012B-4GL-X41-B-E		AP-Q012A-WL-X41-B-WIFI	
system	Main Processor	Dual-core 32-bit DSP(GK7202V300), pure hard compression, watchdog	Dual-core 32-bit DSP(GK7202V200), pure hard compression, watchdog
	image sensor	1/3 inch low illumination CMOS sensor	
	Operation System	Embedded LINUX operating system	
	Video Compression	H.265AI	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	4MP	
	Image resolution	Main code stream: 2560*1440@12fps; Substream: 640*360@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
	Lens	3.6mm	
	Turn video	Flip up and down/flip left and right	
lighting	Light control mode	Night vision Infrared/Night vision Full color	
	Number of lights	6 red lights +6 white lights	
PTZ	PTZ control	Rotation Angle level :340°; Vertical :90°	
	Turn PTZ	Flip up and down/flip left and right	
Audio	Coding standard	G.711	
	Mitou	support	
	Two-way Speech	support	
Record management	Record Mode	Manual video recording, dynamic detection video, alarm	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (128GB Max)	
	Remote playback	support	
	Image capture	support	
Network	frequency band	LTE FDD B1/B3/B7/B8/B20/B28	/
	Connect APP	Scan connection	
extension	Reset key	support	
	solar panel	3W	
	battery	6000MHA	
	Power	DC 5V	
work environment	Suitable place	outdoor、 Home、 shop、 School、 factory;	
	Installation mode	Wall hanging, lifting, flat	
	Working	0℃ – +55℃	
	Working humidity	10% – 90%	

