Model:



- *2+2+4MP PTZ camera (without TF card) X 1
- * Instruction manual X1
- * Power adapter X1
- * Screw pack X1



		Specification parameter
system	Main Processor	Dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog
	image sensor	2 * 1/3+1/2.9 inch low light CMOS sensor
	APP	ICSEE (Android and IOS support)
Video	High Definition	2+2+4MP
	Image resolution	Ball machine: Main stream: 2560* 1440@12fps; Sub stream: 800* 448@12fps Gun mechanism 1: Main stream: 1920* 1080@12fps Sub stream: 640* 360@12fps Gun Machine 2: Main Stream: 1920* 1080@12fps Sub stream: 640* 360@12fps
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	Lens	3.6mm+3.6mm
	Humanoid tracking	support
	Gun-ball linkage	support
	Turn video	Flip up and down/flip left and right
	Video Compression	H.265AI
	Light control mode	Starlight full color/infrared night vision/double light alert
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°
	Turn PTZ	Flip up and down/flip left and right
Audio	Coding standard	G.711
	Two-way voice	support
	Mitou	support
	loudspeaker	support
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (256G Max)
	Remote playback	support
	Image capture	support
Network	WIFI	2.4G IEEE 802.11 b/g/n Wi-Fi compliant
	network port	10M/100M adaptive Ethernet port
	Connect APP	Bluetooth connection, scan code connection, Wired connection
extension	Reset key	support
	Power	DC 12V±10%
		Gun mechanism 1 : 2 infrared+2 white light
	LED	Gun mechanism 2 : 2 infrared+2 white light
		Ball machine: 10 light dual core
work environment	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging
	Working	-20℃−+55℃
	Working humidity	10%-90%