


Model:		3MP Camera (No TF Card) X 1 * DC 12V power adapter X1 * Instructions X1 * Screw bag X1		
AP-A8-4G-X31-SEA				
Specification parameter				
system	Main Processor	Dual-core 32-bit DSP (GK7201V200), pure hard compression, watchdog		
	image sensor	High performance CMOS sensor		
	APP	ICSEE (Android and IOS support)		
Video	High Definition	3MP		
	resolution ratio	Main stream: 2304*1296@12fps; Substream: 800*448@12fps		
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR		
	Lens	3.6mm		
	Humanoid tracking	support		
	Turn video	Flip up and down/flip left and right		
	Video Compression	H.265AI		
PTZ	PTZ control	Rotation Angle level :350°; Vertical :90°		
	Turn PTZ	Flip up and down/flip left and right		
Audio	Coding standard	G.711		
	Two-way voice	support		
	Mitou	support		
	loudspeaker	support		
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video		
	Video storage	TF card/cloud		
	storage	Cloud Storage +TF Local Video recording (128GB Max)		
	Remote playback	support		
	Image capture	support		
Network	network port	10M/100M adaptive Ethernet port		
	4G	LTE FDD B1/B3/B5/B8 LTE TDD B34/B38/B39/B40/B41		
	Connect APP	4Gscan code connection		
extension	Reset key	support		
	LED	8LED		
	Power	DC 12V		
work environment	Suitable place	outdoor、Home、shop、School、factory;		
	Installation mode	Wall hanging		
	Working	-10℃ — +55℃		
	Working humidity	10% — 90%		

