



| Model                  |                                                                                                                           | AP-L2004B-X3 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------|--------------|
| Chip:                  | Dual-core 32-bit DSP (GK7202V300)                                                                                         |              |
| Sensor size            | High-performance low-light CMOS sensor                                                                                    |              |
| Resolution             | 2560*1440                                                                                                                 |              |
| Video processing       | H.265AI encoding, dual stream, AVI format; stream 0.1M~10Mbps adjustable; frame rate 1~30 frames/second                   |              |
| Image output           | Main stream: 2560*1440@12fps; sub-stream: 800*448@12fps                                                                   |              |
| Audio processing       | G.711A codec standard, supports two-way voice intercom function, supports audio and video synchronization                 |              |
| Audio output           | 1 input, level 2Vp-p, impedance 1k $\Omega$ ,; 1 output, impedance 16 $\Omega$ , 30mw output power (audio alarm interface |              |
| APP                    | icsee (Super See)                                                                                                         |              |
| Network interface      | Wireless connection                                                                                                       |              |
| Infrared night vision  | 4 lights                                                                                                                  |              |
| Y                      | Built-in left and right, up and down motors                                                                               |              |
| Reset button interface | Support one-button reset                                                                                                  |              |
| Storage method         | Local TF card storage, maximum 128G; cloud storage                                                                        |              |
| Networking method      | Support 4G network connection                                                                                             |              |
| ONVIF protocol         | Not supported                                                                                                             |              |
| Mobile monitoring      | Support mobile monitoring (iOS, Android)                                                                                  |              |
| Reliability            | Full lightning protection, in line with national and international standards; 7*24 hours 65℃ high                         |              |
| Business function      | Support multiple cloud technologies, realize network penetration, push alarm information to mobile phones and             |              |
| Intelligent analysis   | Support PIR human body sensing, support customization of other intelligent functions                                      |              |
| Lens                   | 3.6MM                                                                                                                     |              |
| Power supply           | DV5V $\pm$ 10%                                                                                                            |              |
| Solar panel            | 3W                                                                                                                        |              |
| Battery capacity       | 6000mAh                                                                                                                   |              |
| Color box size         | 221*176*121 (MM)                                                                                                          |              |
| Outer box size         | 45.7*37*62.5 (CM) 20PCS/box                                                                                               |              |