


Model:		<div> <div>AP-Q014B5-4GL-X41-B-SA</div> <div> *4MP battery binocular camera (TF card not include) * Instruction manual X1 * Screw pack X1 * Bracket X1 * 1 m power cord X1 </div> <div>  </div> </div>
Specification parameter		
system	Main Processor	dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog
	image sensor	Two 1/3 "low illumination CMOS sensors
	Operation System	Embedded LINUX operating system
	Video Compression	H.265AI
	APP	ICSEE (Android and IOS support)
Video	High Definition	2+2MP
	Image resolution	Main stream: 2560*1440@12fps; Substream: 800*448@12fps
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	Lens	3.6+3.6mm
	Turn video	Flip up and down/flip left and right
lighting	Light control mode	Night vision Infrared/Night vision Full color
	Number of lights	Gun machine: 4 lamp double core, ball machine: 6 lamp double
PTZ	PTZ control	Rotation Angle level :300°; Vertical :90°
	Turn PTZ	Flip up and down/flip left and right
Audio	Coding standard	G.711A
	Mitou	support
	Two-way Speech	support
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video
	Video storage	TF card/Cloud
	storage	Cloud storage +TF local recording (128GB Max)
	Remote playback	support
	Image capture	support
Network	frequency band	LTE FDD B1/B3/B5/B8/B34/B38/B39/B40/B41
	Connect APP	Scan connection
extension	Reset key	support
	solar panel	3W
	battery	9000MHA
	Power	DC 5V
work environment	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging, lifting
	Working	0℃ — +55℃
	Working humidity	10% — 90%

