


<b>Model:</b>  <div>AP-Q022-4GW-X41-B-E</div>		*2+2MP low-power dual beam camera (excluding TF card) X 1 *Solar panel x1 *Instruction manual X1 *Screw package X1 
Specification parameter		
system	Main Processor	Dual-core 32-bit DSP (RV1106G2), pure hard compression, watchdog
	image sensor	Two 1/3 "low illumination CMOS sensors
	APP	ICSEE (Android and IOS support)
Video	High Definition	2+2MP
	Image resolution	Main stream: 1920*2160@12fps; Substream: 800*896@12fps
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	Lens	3.6mm+3.6mm
	Humanoid tracking	support
	Gun-ball linkage	support
	Turn video	Flip up and down/flip left and right
	Video Compression	H.265AI
	Light control mode	Starlight full color/infrared night vision/double light alert
PTZ	PTZ control	Rotation Angle level :340°; Vertical :90°
	Turn PTZ	Flip up and down/flip left and right
Audio	Coding standard	G.711A
	Two-way voice	support
	Mitou	support
	loudspeaker	support
Record management	Record Mode	Support 1-second 1-frame recording (AOV state)+full frame rate recording (wake-
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (256GB Max)
	Remote playback	support
	Image capture	support
Network	4G	LTE FDD B1/B3/B5/B7/B8/B20/B28
	Connect APP	QR code connection
extension	Reset key	support
	Power	DC 5V
	Solar panels	8W
	Battery	9000mah
	LED	Gun mechanism: 10-light dual core, ball mechanism: 6-light dual core
work environment	Suitable place	Outdoor open spaces
	Installation mode	Wall hanging
	Working	-10℃ — +45℃
	Working humidity	10% — 90%

