


<b>Model:</b> <div> AP-Q042-4GL-X42-E </div>		*4MP 4G low-power camera (excluding TF card) * Instruction manual X1 * Screw pack X1 * Bracket X1 * 3 m power cord X1	
Specification parameter			
system	Main Processor	RV1106G2	
	image sensor	1/3 inch low illumination CMOS sensor	
	Operation System	Embedded LINUX operating system	
	Video Compression	H.265AI	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	4MP	
	Image resolution	Main code stream: 2560*1440@12fps; Substream: 800*448@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR	
	Mobile Tracking	support	
	Lens	3.6mm	
	Turn video	Flip up and down/flip left and right	
lighting	Light control mode	Starlight full color/intelligent warning/infrared night vision	
	Number of lights	4 red lights +4 white lights	
PTZ	PTZ control	Rotation Angle level :340°; Vertical :90°	
	Turn PTZ	Flip up and down/flip left and right	
Audio	Coding standard	G.711	
	Mitou	support	
	Two-way Speech	support	
Record management	Record Mode	Supports 24-hour video recording, supports 1-second 1-frame recording (AOV state)+full frame rate recording (wake-up state)	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (512GB Max)	
	Remote playback	support	
	Image capture	support	
Network	frequency band	LTE FDD B1/B3/B5/B7/B8/B20/B28	
	Connect APP	Scan connection	
extension	Reset key	support	
	solar panel	8W	
	battery	9000MHA	
	Power	DC 5V	
work environment	Suitable place	outdoor、Home、shop、School、factory;	
	Installation mode	Wall hanging	
	Working	0℃— +55℃	
	Working humidity	10%—90%	

