## Model:

## **AP-**B246-**W-S21B AP-**B246-**W-S31B AP-**B246-**W-S51B**

\* Camera (No TF Card) X 1 \* Power plug X1 \* Instructions X1

\* Screw bag X1



Specification parameter				
	MODEL	<b>AP-</b> B246 <b>-W-S21B</b>	<b>AP-</b> B246 <b>-W-S31B</b>	<b>AP-</b> B246 <b>-W-S51B</b>
system	Main Processor	AK3918EV200	AK3919EV330L	AK3918EV331
	image sensor	SC1345	Q03B	SC3336
	Operation System	Embedded LINUX OS system		
Video	High Definition	1080P/3MP/5MP		
	Video Compression	Н.265		
	Rotation angle	Horizontal:355°; vertical: 90°		
	Object tracking	Support		
	low illumination	0.1LUX/F1.2		
	picture Capture	Support		
	Video Flip	Support		
Audio	Coding standard	G.711		
	Two-way Speech	Support		
Record management	Video file size	2.5GB-9GB/Day		
	Record Mode	Manual record, motion detection record, alarm record		
	Video storage	TF Card/Cloud		
	playback, back up	Support		
	Alarm trigger	Video Push, Alarm recording, screen shot capture		
Network	Network Interface	NO		
	WIFI	Wifi 2.4G+5G		
	Network Protocol	Support TCP/IP, RTSP, etc		
	transmission mode	P2P, Smart Cloud Sever		
	WIFI connection	Sweep QR code, AP Hotspot Addition		
extend	TF Card	Maximum support 256GB TF card		
	Reset key	Support		
power supply	Power	DC 5V		
	Power consumption	≤5W		
work environment	Suitable place	Home, shop, School, factory;		
	Installation mode	Flat put, Wall mounted, hoisting		
	Working Temperature	-10°C -+ 55°C		
	Working humidity	10%-90%		
Other	Camera lens	3.6MM		
	Lamp board	2 pcs		