

Model:		2MP/3MP/5MP Camera (No TF Card) X 1 * DC 5V 1A power adapter X1 * 1 m power cord X1 * Bracket X 1 * Instructions X1 * Screw bag X1			
AP-B325-W-X21B AP-B325-W-X31B AP-B325-W-X41B					
Specification parameter					
Model No.		AP-B325-W-X21B	AP-B325-W-X31B	AP-B325-W-X41B	
system	Main Processor	Dual-core 32-bit DSP (GK7201V300), pure hard	Dual-core 32-bit DSP (XM533), pure hard	Dual-core 32-bit DSP (GK7202V300), pure hard	
	image sensor	1/4-inch low illumination CMOS sensor	High performance CMOS sensor	1/2.8 inch low illumination CMOS sensor	
	APP	ICSEE (Android and IOS support)			
Video	High Definition	2MP	3MP	4MP	
	resolution ratio	Main stream: 1920*1080@12fps; Substream: 800*448@12fps	Main stream: 2304*1296@12fps; Substream: 800*448@12fps	Main stream: 2560*1440@12fps; Substream: 640*360@12fps	
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR			
	Lens	3.6mm			
	Humanoid tracking	support			
	Turn video	Flip up and down/flip left and right			
	Video Compression	H.265AI			
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°			
	Turn PTZ	Flip up and down/flip left and right			
Audio	Coding standard	G.711			
	Two-way voice	support			
	Mitou	support			
	loudspeaker	support			
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video			
	Video storage	TF card/cloud			
	storage	Cloud Storage +TF Local Video recording (128GB Max)			
	Remote playback	support			
	Image capture	support			
Network	WIFI	2.4G IEEE 802.11 b/g/n			
	Connect APP	Bluetooth connection, scan code connection			
	ONVIF	support			
extension	Reset key	support			
	LED	6 infrared			
	Power	DC 5V			
work environment	Suitable place	outdoorHomeshopSchoolfactory;			
	Installation mode	Wall hanging, lifting, flat			
	Working Temperature	-20℃ — +55℃			
	Working humidity	10%—90%			