


Model:		2MP/3MP/5MP Camera (No TF Card) X 1 * DC 5V 1A power adapter X1 * 1 m power cord X1 * Bracket X 1 * Instructions X1 * Screw bag X1		
<div>AP-B688B-W-X21B AP-B688B-W-X31B AP-B688B-W-X41B</div>				
Specification parameter				
Model No.		AP-B688B-W-X21B	AP-B688B-W-X31B	AP-B688B-W-X41B
system	Main Processor	Dual-core 32-bit DSP (GK7201V300), pure hard	Dual-core 32-bit DSP (XM533), pure hard	Dual-core 32-bit DSP (GK7202V300), pure hard
	image sensor	1/4-inch low illumination CMOS sensor	High performance CMOS sensor	1/2.8 inch low illumination CMOS sensor
	APP	ICSEE (Android and IOS support)		
Video	High Definition	2MP	3MP	4MP
	resolution ratio	Main stream: 1920*1080@12fps; Substream: 800*448@12fps	Main stream: 2304*1296@12fps; Substream: 800*448@12fps	Main stream: 2560*1440@12fps; Substream: 640*360@12fps
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR		
	Lens	3.6mm		
	Humanoid tracking	support		
	Turn video	Flip up and down/flip left and right		
	Video Compression	H.265AI		
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°		
	Turn PTZ	Flip up and down/flip left and right		
Audio	Coding standard	G.711		
	Two-way voice	support		
	Mitou	support		
	loudspeaker	support		
Record management	Record Mode	Manual video recording, dynamic detection video, alarm video		
	Video storage	TF card/cloud		
	storage	Cloud Storage +TF Local Video recording (128GB Max)		
	Remote playback	support		
	Image capture	support		
Network	WIFI	2.4G IEEE 802.11 b/g/n		
	Connect APP	Bluetooth connection, scan code connection		
	ONVIF	support		
extension	Reset key	support		
	LED	6 infrared		
	Power	DC 5V		
work environment	Suitable place	outdoorHomeshopSchoolfactory;		
	Installation mode	Wall hanging, lifting, flat		
	Working Temperature	-20℃ — +55℃		
	Working humidity	10%—90%		