## Model:

AP-Q014-WL-X41-B

- \*4MP battery binocular camera (TF card not included) x 1
- \* Instruction manual X1
- \* Screw pack X1
- \* Bracket X1
- \* 1 m power cord X1



Specification parameter							
system	Main Processor	core 32-bit DSP (XM650V200), pure hard compression, water					
	image sensor	Two 1/3 "low illumination CMOS sensors					
	Operation System	Embedded LINUX operating system					
	Video	H.265AI					
	APP	ICSEE (Android and IOS support)					
Video	High Definition	2+2MP					
	Image resolution	Main stream: 2560*1440@12fps; Substream: 800*448@12fps					
	Minimum illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IF					
	Lens	3.6+3.6mm					
	Turn video	Flip up and down/flip left and right					
lighting	Light control mode	Night vision Infrared/Night vision Full color					
	Number of lights	Gun machine: 4 lamp double core, ball machine: 6 lamp					
PTZ	PTZ control	Rotation Angle level :300°; Vertical :90°					
	Turn PTZ	Flip up and down/flip left and right					
Audio	Coding standard	G.711A					
	Mitou	support					
	Two-way Speech	support					
Record management	Record Mode	Manual video recording, dynamic detection video, alarm					
	Video storage	TF card/Cloud					
	storage	Cloud storage +TF local recording (128GB Max)					
	Remote playback	support					
	Image capture	support					
Network	WIFI	2.4G WIFI 802.11b/g/n					
	Connect APP	WiFi scanning code distribution network					
extension	Reset key	support					
	solar panel	3W					
	battery	9000MHA					
	Power	DC 5V					
work environment	Suitable place	outdoor、Home、shop、School、factory;					
	Installation mode	Wall hanging, lifting					
	Working	0℃−+55℃					
	Working humidity	10%-90%					